

Section _____

HV Outer sheath

Application _____

Field

Laboratory

**PRODUCT BENEFITS**

Switch from longitudinal cut to circular cut without removing the tool from the cable
 Sound alert when the blade is touching the aluminium/lead shield
 Very fine tuning of the cutting depth

TOOL CAPACITY

Diameter	40 - 90 mm 1,575 - 3,543 inch
-----------------	----------------------------------

Screen thickness capacity	11 mm / 0,433 in
----------------------------------	------------------

TOOL DIMENSIONS

Length	370 mm
Width	155 mm
Height	470 mm
Weight without box	7,7 Kg
Packaging	Case

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
 FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Stripping tool for HV and EHV cable's outer sheath and shield

TO DO WHAT

The DMSR/40-90 enables the user to remove the outer sheath and the aluminium/lead shield on HV and EHV cable by successively performing a longitudinal and circular cut

With an embedded mechanical dial gauge the user scores the aluminium shield without cutting through it

**Spare part**

LDMS38 - Spare blade for outer sheath and shield

BE-DMSR - Shield detection device

205130 - Conductive aluminium tape

Associated tool

EGA - HV and EHV cable's outer sheath and shield spreaders

EV HTB - HV and EHV cable's outer sheath and shield splitters

EVP - HV and EHV cable's lead sheath splitters

HV cables Tools

DMSR/40-90



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Screen thickness capacity	Length	Width	Height	
DMSR/40-90	40 - 90 mm 1,575 - 3,543 in	11 mm / 0,433 in	370 mm 14,567 in	155 mm 6,102 in	470 mm 18,504 in	case
DMSR/80-160	80 - 160 mm 3,150 - 6,299 in	11 mm / 0,433 in	400 mm 15,748 in	160 mm 6,299 in	530 mm 20,866 in	case