

CWP Cable Gland Kits

CW Premium Cable Gland Kits



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Standard BS EN 62444:2013, BS 6121 Part-1 1989, EN 50262:1999

Application External or internal for use with all types on SWA armoured cables

Providing Environmental seal on the cable outer sheath, also provides mechanical cable retention and electrical continuity via armoured wire Termination

Function wire Termination

Ingress Protection IP66 (with thread seal) EN60529

Brass (Nickle plated versions, aluminium or stainless steel available upon request)

Material LSF PVC

Shroud LSF PVC

Seals PCP (Black)

Thread Metric

Operating Temperature Standard Seals -20° C to + 80° C

Kit Contents Brass Gland, Brass Locknut, Brass Earth Tag Nylon Thread Seal, LSF Shroud (M16-M32 2 per kit, M40-M90 1 per kit)

Gland Size Ref.	Entry Threads		Cable Acceptance Details				Hexagonal Details	
	Dia	Length	Below Armour	Outer Dia Min	Outer Dia Max	Armour Wire Dia.	Flats	Corners
CWP16	16	10	9.0	8.4	13.8	0.9	22.0	24.4
CWP20SS	20	10	9.0	8.4	13.8	0.9	22.0	24.4
CWP20S	20	10	11.8	12.9	15.8	0.90/1.25	24.0	26.6
CWP20	20	10	13.8	15.5	20.8	0.90/1.25	30.0	33.3
CWP25	25	10	19.8	20.3	37.5	1.25/1.60	38.0	42.2
CWP32	32	10	26.4	26.7	33.5	1.60/2.00	46.0	51.0
CWP40	40	15	32.4	33.0	40.9	1.60/2.00	55.0	61.0
CWP50S	50	15	38.0	39.4	46.3	2.00/2.50	60.0	66.6
CWP50	50	15	44.0	45.7	52.6	2.00/2.50	65.0	72.1
CWP63S	63	15	49.0	52.1	61.5	2.5	75.0	83.2
CWP63	63	15	55.5	58.4	65.3	2.5	80.0	88.8
CWP75S	75	20	62.0	64.8	73.0	2.5	90.0	100.0
CWP75	75	20	67.0	71.0	78.0	2.5	95.0	105.4
CWP90	90	20	79.0	81.0	90.0	2.50/3.15	110.0	122.1

Dimensions are in millimeters