

3M™ IEC-Separable Connectors

Asymmetrical T- Type Connectors 630A 1250A Umax 36kV

IEC-Separable Product Family

Technical Datasheet



Product Description

The IEC-Separable 630A and -1250A Kit Series consist of an EPDM Asymmetrical T-Type Separable Connector. The assembly is touch safe, has an integrated Silicone Adapter Tube as refractive stress controlling part and an integrated capacitive test point in the insulation plug. Each kit contains all the necessary components to install Plug-In to a 3-Phase system, including all connection devices.

Applications

These Kits are designed to be installed on wire screened non-armored polymeric insulated cables for 18/30 kV and 19/33 kV (Umax = 36 kV) - 630A / -1250A and applications. With additional supplementary earthing kits, the installation on cable types with Copper Tape -, Aluminum Tube - or Copper Wire and Aluminium Laminate – screened cables are possible. The IEC-Separable Connector establishes the connection between any polymeric insulated cable onto transformers, switch gears, motors or other equipment.

Typical Properties

The one-piece design of the Separable Connector is made of EPDM rubber. It guarantees a watertight connection and a long-life span for cable ends. It is suitable for outer cone bushings according to DIN EN 50180 and DIN EN 50181.

Performance Tests

Meets European standard specifications:
Cenelec HD 629.1 S3:2018 (DIN VDE 0278, part 629-1).

Test Reports available on request.

Electrical Ratings	Values
Max. System Voltage	36 kV
Impulse	194 kV
AC Withstand (5 min.)	85,5 kV
Continuous Current	630 A / 1250 A

User Information

Selection Guide T-Plug

Kit Reference	Amps	Min. Diameter over Primary Insulation (mm)	Voltage Class (U max)	Dimensions (mm)		
			36 kV			
			Nominal Cross Section (mm ²)*	H	L	W
IEC Separable T-Plug Front						
EE-36-CW1-T-C1-A3-S1 3-Phase 1/CV	630A	21.0 - 30.0	25-95	287	174	85
EE-36-CW1-T-C1-B3-S2 3-Phase 1/CV	630A	27.3 - 38.5	120-300	287	174	85
EE-36-CW1-T-C2-C3-S3 3-Phase 1/CV	1250A	38.5 - 50.0	400-630	356	174	93
IEC Separable T-Plug Rear (Sub-T Plug)						
EE-36-CW1-R-C1-A3-S1 3-Phase 1/CV	630A	21.0 - 30.0	25-95	288	165	73
EE-36-CW1-R-C1-B3-S2 3-Phase 1/CV	630A	27.3 - 38.5	120-300	288	165	73
EE-36-CW1-T-C2-C3-S3 3-Phase 1/CV	1250A	38.5 - 50.0	400-630	356	174	93

* Check if the diameter over primary insulation is in the appropriate range

Selection Guide Supplementary Earthing Kit

Cable Type (Screen)	94-PAE 610-1 AL-CT	94-PAE 620-1 AL-CT	94-PAE 621-1 CW-ALF
	36 kV max	36 kV max	36 kV max
Copper Tape	up to 150mm²	150mm² - 630mm²	N/A
Aluminium Tube	up to 150mm²	150mm² - 630mm²	N/A
Copper Wire / Alum. Laminate	N/A	N/A	up to 630mm²

Product Identification

3M Asymmetrical T-Type Separable Connector kits are marked with supplier name, cable cross section ranges, voltage class and cable type, storage conditions and manufacturing codes for product traceability.

Shelf Life and storage

The 3M™ Asymmetrical T-Type Separable Connectors have a 60-month shelf life from date of production, stated on the label, when stored in a humidity-controlled storage (-40°C up to 50°C and <70% relative humidity).

Additionally, the expiring date is stated on the carton label.

Additional Information

To request additional product information, see address below.

Legal information

WEEE, RoHS and REACH information

3MTM IEC-Separable are not considered in scope of Directive 2012/19/EU (Waste electrical and electronic equipment (WEEE)) and Directive 2011/65/EU (Restriction of the use of certain hazardous substances in electrical and electronic equipment).

3MTM IEC-Separable do not contain the substances listed in Annex II of 2011/65/EU (RoHS) or REACH SVHC (EC) 1907/2006 (REACH) per June 2025.

Please visit the 3M website or contact your local representative for the latest regulatory status.

Source of Supply

3M Marcallo/Italy

Important Notice

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third-party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labelled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labelled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

3M Electrical Markets Division

3M Deutschland GmbH
Carl-Schurz-Str.1
41453 Neuss
Germany

Reference: 78-9237-9082-4_B

Issue date: 20.05.2026 – Supersedes

© 3M 2026. 3M is trademark of 3M. All rights reserved.