


Mounting accessory

External coupler

Type	Dimensions Height x Width x Length (mm)			Weight (g)	Cat. no.
------	---	--	--	------------	----------

External coupler system height 60 and 110 to be used to joint two lengths of Fibre-Optic Duct. Fixation with bolts M6x16, nuts & star washers. Use 2 couplers per duct. Material: steel, pre-galvanized, powder coated RAL1023.



Height = 60 mm	H	W	L		
External coupler	60	10	200	129	CSU7605000FS123
Height = 110 mm	H	W	L		
External coupler	110	10	200	200	CSU7105000FS123

Internal coupler (Unilock)

Type	Dimensions Height x Width x Length (mm)			Weight (g)	Cat. no.
------	---	--	--	------------	----------

Screwless snap-in internal coupler for system height 60 to be used to joint two lengths of Fibre-optic duct. Optional fixation with bolts M6x16, nuts and star washers. Use 2 couplers per duct. Material: steel, pre-galvanized.




Height = 60 mm	H	W	L		
Internal coupler (screwless)	21	55	175	82	CSU08010109

Internal coupler

Type	Dimensions Height x Width x Length (mm)			Weight (g)	Cat. no.
------	---	--	--	------------	----------

Internal coupler for system height 110 to be used to joint two lengths of Fibre-Optic Duct. Fixation with bolts M6x16, nuts and star washers. Use 2 couplers per Duct. Material: steel, pre-galvanized.




Height = 110 mm	H	W	L		
Internal coupler	1.5	106.5	300	365	CSU71030100

Hinge coupler

Type	Dimensions Height x Width x Length (mm)			Weight (g)	Cat. no.
------	---	--	--	------------	----------

Can be used to construct any type of level change at any point of the Fibre-Optic Duct installation. Use 2 couplers per Duct. To be used in combination with bolts M6x16, nuts and star washers. Material: steel, pre-galvanized, powder coated RAL1023.



Height = 60 mm	H	W	L		
Hinge coupler	11	63	234	150	CSU0875000FS123
Height = 110 mm	H	W	L		
Hinge coupler	12	114	230	406	CSU0875100FS123

Bottom coupler

Type	Dimensions Height x Width x Length (mm)			Weight (g)	Cat. no.
------	---	--	--	------------	----------

Optional sleeve-on bottom coupler for enhanced system alignment. Material: steel, pre-galvanized, powder coated RAL1023.



	H	W	L		
Bottom coupler 200	1	100	170	130	CSU7070200FS123
	H	W	L		
Bottom coupler 300	1	100	270	209	CSU7070300FS123

Bolt

Type	Dimensions Height x Width x Length (mm)			Weight (g)	Cat. no.
------	---	--	--	------------	----------

M6x16 bolts delivered in a bag of 100 pieces. Material: steel, electro-galvanized.



	H	W	L		
M6x16 bolt (pack of 100)	-	-	16	100	CSU08463000

Mounting accessory (cont.)

Flange nut

Type	Weight (g)	Cat. no.
Flange nuts delivered in a bag of 100 pieces. Material: steel, electro-galvanized.		
 M6 flange nut (pack of 100)	311	CSU08461000
M10 flange nut (pack of 100)	1200	CSU08890100

Star washer

Type	Weight (g)	Cat. no.
Star washer to be used in combination with bolt (ref: CSU08463000) and M6 nut (ref: CSU08461000) to ensure electrical continuity throughout the system when connecting different system components. Ensure use of star washer on all painted surfaces. Delivered in a bag of 100 pieces. Material: steel, electro-galvanized.		
 M6 star washer (pack of 100)	323	CSU08190001

Universal cover clip

Type	Dimensions Height x Width x Length (mm)	Weight (g)	Cat. no.
Universal cover clip for snap-on fixation of the covers. Delivered in a bag of 100 pieces. Material: spring steel.			
	H W L		
Universal cover clip (pack of 100)	15 13 15	289	CSU08855000


Modular cable retainer

Type	Dimensions Height x Width x Length (mm)	Weight (g)	Cat. no.
Suited with double sided self-adhesive tape to be fixed inside the duct. Delivered in 10 cm pieces in a bag of 50.			
	H W L		
Modular cable retainer (pack of 50)	5.5 25 96	8	718469

Protection strip

Type	Dimensions Height x Width x Length (mm)	Weight (g)	Cat. no.
Protection strip. To be used to protect cutted edges in the cable duct. Delivered as roll of 5 m. Material: PVC, black.			
	H W L		
Protection strip	- - 5000	342	CSU08040000

Earthing kit

Type	Dimensions Height x Width x Length (mm)	Weight (g)	Cat. no.
Kit including earth wire with flat pin connectors and earthing clamps. Connect to 2 cover pieces to ensure electrical continuity between each other. Delivered in a bag of 10 pieces.			
	H W L		
Earthing kit (Pack of 10)	- - 200	10	ISM10953