

KB284 Cable trays

Zinc+ Support system

Support system

Type	Dimensions A/B (mm)	Length C (mm)	Weight kg/pcs	Ref. No.
------	------------------------	------------------	------------------	----------

Suspension beam

Suspension beam for double-threaded rod suspended installation. Use bolts M6x10, nuts to fix cable tray to the beam.
Finish: steel, Hot dip galvanized

Suspension beam 100	100			791063
Suspension beam 200	200			791064
Suspension beam 300	300			791065
Suspension beam 400	400			791066
Suspension beam 500	500			791067
Suspension beam 600	600			791068

C-Bracket

C-bracket for single central suspended threaded rod installation. Use bolts M6x10, nuts to fix cable tray to the bracket.
Finish: steel, Hot-dip galvanized.

C-Bracket Medium 100	100			CSU08173100
C-Bracket Medium 150	150			CSU08171500
C-Bracket Medium 200	200			CSU08173200
C-Bracket Medium 300	300			CSU08173300
C-Bracket Heavy 400	400			CSU14174000
C-Bracket Heavy 500	500			CSU14175000
C-Bracket Heavy 600	600			CSU14176000

Cantilever arms

Cantilever arm to be used for mountings on walls, vertical pieces or pendant/fixing rails.
Finish: steel, Hot-dip galvanized.

Cantilever arm 50i 100	100			CSU795316
Cantilever arm 50i 200	200			CSU795317
Cantilever arm 50i 300	300			CSU795318
Cantilever arm 50i 400	400			CSU795319
Cantilever arm 50i 500	500			CSU795320
Cantilever arm 50i 600	600			CSU795321

Cantilever arm 50

Cantilever arm for mounting on walls, pendant/fixing rails or vertical pieces.
Finish: Steel, hot-dip galvanized.

50-100	85/150/40	24	7321677234325	723432
50-150	85/200/40	28	7321677234332	723433
50-200	85/250/40	34	7321677234349	723434
50-250	105/300/40	52	7321677234356	723435
50-300	105/350/40	60	7321677234363	723436
50-400	120/450/50	228	7321677234370	723437
50-500	140/550/50	172	7321677234387	723438
50-600	150/650/50	215	7321677234394	723439

Threaded rod

Threaded rod for suspended installations.
Finish: steel, Zinc flake.

Threaded rod M10	M10	2000		CSU08051020
------------------	-----	------	--	-------------

Nut and washer

For fastening of threaded rod to bracket / C bracket.
Finish: steel, Zinc flake.

Nut M10	M10			CSU08890120
Washer M10	M10			CSU08900020

KB284 Cable trays

Zinc+ Support system

Support system



CSU08020200.jpg

Type	Dimensions A/B (mm)	Length C (mm)	Weight kg/pcs	Ref. No.
Ceiling attachment-open				
Use ceiling bracket for plain ceiling. Fix rod with two pieces of M10 nuts. Finish: steel, Hot-dip galvanized.				
Ceiling attachment-open				CSU08020200



P133938.eps

Vertical piece 2F				
Length of the pendant can be extended by using pendant fixing rail 24/48 and rail connector 2FJ. Finish: steel, Hot-dip galvanized.				
Vertical piece 2F 280	280			717196
Vertical piece 2F 370	370			717197
Vertical piece 2F 505	505			717198
Vertical piece 2F 640	640			CSU794202
Vertical piece 2F 730	730			717199
Vertical piece 2F 865	865			CSU794203
Vertical piece 2F 1000	1000			717200
Vertical piece 2F 1500	1500			787276



P133942.eps

Vertical piece 20 Double				
Vertical piece, two-sided, to be used for vertical installation together with Cantilever arm 50, from a ceiling or on a floor. Can also be installed as a cantilever arm on a wall. Finish: steel, Hot-dip galvanized.				
Vertical piece 20 Double 280	280			CSU794204
Vertical piece 20 Double 370	370			CSU794205
Vertical piece 20 Double 505	505			715723
Vertical piece 20 Double 640	640			CSU794206
Vertical piece 20 Double 730	730			715724
Vertical piece 20 Double 865	865			CSU794207
Vertical piece 20 Double 1000	1000			715725
Vertical piece 20 Double 1495	1495			715726



P140069.eps

End Plug 28E				
High visibility end plug for enhanced safety and easy identification. Finish: PP/TPE, orange.				
End Plug 28D				709020
End Plug 28E				709021



T-Bolt				
Bolts, nuts and washers are delivered in a bag of 100 pieces. Finish: steel, Hot-dip galvanized				
T-bolt 26U M8	M8x30	30		CSU795595
T-bolt 26U M10	M10x30	50		CSU795589
T-bolt 26U M10	M10x40	60		CSU795590